



### QC CL-4700 Specifications

Motor Voltage	120 VAC, 60 Hz
Energy Use	Hi: 632 Watts Low: 459 Watts
Air Flow	Hi: 4505 CFM Low: 3598 CFM
Square Foot Coverage @ 2 CFM per SQ FT	Covers up to 2250 SQ FT
# of Speeds	2
Duct Diameter	18"
Duct Length	9 feet
Motor Head Diameter	18 1/2"
Motor Head Length	13 1/2"
Sound Level in Room (measured 1m from grille)	Hi: 51 dB Low: 48 dB
Dampers	Barometric Pressurized R5 Dampers
Controls (not included)	8 Hour Electronic Timer and HI-LOW-OFF Switch or Wi-Fi Smart Control (not included)
Warranty	10 Years
Framing	None required
Joist Cutting	None required; fits 16" or 24" on center
Minimum Suggested Attic Venting	6.0 SQ FT net free area
Ceiling Rough Opening	14 1/4" X 30 1/4"
Removable Grille Outside Dimension	16" x 32"
Shipping Weight	64 lbs.
Box Dimensions	40" x 22" x 36"
In the Box	- QC CL-4700 Motorhead - Damper Box - Ceiling Grille - 9 foot duct - Cut-out template - Accessory bag - Window locks