



QC STL PRO-5.5 Specifications

Motor Voltage	120 VAC, 60 Hz
Energy Use	Hi: 724 Watts Med: 244 Watts Low: 82 Watts
Air Flow	Hi: 5688 CFM Med: 4049 CFM Low: 2719 CFM
Square Foot Coverage @ 2 CFM per SQ FT	Covers up to 2800 SQ FT
# of Speeds	3
Duct Diameter	20"
Duct Length	9 feet
Motor Head Diameter	20 1/2"
Motor Head Length	13 1/2"
Sound Level in Room (measured 1m from grille)	Hi: 50 dB Med: 43 dB Low: 41 dB
Dampers	Barometric Pressurized R5 Dampers
Controls	Included 8 Hour Electronic Timer and Double 3-Way Switch
Warranty	15 Years
Framing	None required
Joist Cutting	None required; fits 16" or 24" on center
Minimum Suggested Attic Venting	7.6 SQ FT net free area
Ceiling Rough Opening	14 1/4" X 30 1/4"
Removable Grille Outside Dimension	16" x 32"
Shipping Weight	76 lbs.
Box Dimensions	42" x 24" x 38"
In the Box	- QC STL PRO-5.5 Motorhead - Controls - Damper Box - Removable Grille - 9 foot duct - Cut-out template - Accessory bag - Window locks