



QC STL PRO-6.5 Specifications

Motor Voltage	120 VAC, 60 Hz
Energy Use	Hi/Hi: 569 Watts Hi/Lo: 344 Watts Hi/Off: 266 Watts Lo/Off: 76 Watts
Air Flow	Hi: 6035 CFM Med/Hi: 4897 CFM Med/Low: 3630 CFM Low: 2323 CFM
Square Foot Coverage @ 2 CFM per SQ FT	Covers up to 3000 SQ FT
# of Speeds	4
Duct Diameter	16"
Duct Length	6 feet
Motor Head Diameter	16 1/2"
Motor Head Length	13 1/2"
Sound Level in Room (measured 1m from grille)	Hi: 50 dB Med/Hi: 48 dB Med/Low: 45 dB Low: 43 dB
Dampers	Barometric Pressurized R5 Dampers
Controls	Included 8 Hour Electronic Timer and Double 3-Way Switch
Warranty	15 Years
Framing	None required
Joist Cutting	None required; fits 16" or 24" on center
Minimum Suggested Attic Venting	8.4 SQ FT net free area
Ceiling Rough Opening	14 1/4" X 36 1/4"
Removable Grille Outside Dimension	16" x 38"
Shipping Weight	87 lbs.
Box Dimensions	42" x 20" x 38"
In the Box	- QC STL PRO-6.5 Motorheads - Controls - Damper Box - Removable Grille - 6 foot duct (2) - Cut-out template - Accessory bag (2) - Window locks